

TIVAR[®] Sterra[™] ESD UHMW-PE

Ultra High Molecular Weight Polyethylene

mcam.com

TIVAR Sterra ESD Ultra High Molecular Weight Polyethylene UHMW-PE electro static dissipative shapes are produced from re-processed, industrial UHMW materials, and re-purposed for use in a variety of industries such as agriculture and grain handling and bulk material and parcel handling. As a premium grade that is both economical and eco-friendly, TIVAR Sterra ESD UHMW-PE components exhibit excellent abrasion and corrosion resistance, outstanding impact strength, minimal moisture absorption, and a low coefficient of friction. For these reasons, TIVAR Sterra ESD UHMW-PE is often a favored solution for conveyor, chute, and hopper applications, where electrical charge build-ups are prevalent.

As part of the Sterra product portfolio, this material contains recycled content and exhibits a significantly lower carbon footprint compared to similar materials derived from virgin feedstocks.

Recycled Content (post-industrial material)	70%
---	-----

ENVIRONMENTAL PRODUCT DATA SHEET

		TIVAR [®] Sterra [™] ESD UHMW-PE		Comparison with a generic material based on 100% virgin resin	
		Units	Indicative Values	Units	Indicative Values
Life Cycle Impact Assessment Results	Climate change	kg CO ₂ eq / kg product	1.77	kg CO ₂ eq / kg product	3.25
	Acidification	Mole of H ⁺ eq. / kg product	1.91E-03	Mole of H ⁺ eq. / kg product	4.97E-03
	Ecotoxicity freshwater	CTUe / kg product	11.71	CTUe / kg product	34.29
	Particulate Matter	Disease inc. / kg product	2.70E-08	Disease inc. / kg product	4.00E-08
	Human toxicity, non-cancer - total	CTUh / kg product	1.68E-08	CTUh / kg product	5.71E-08
	Resource use, fossils	MJ / kg product	39.89	MJ / kg product	104.36
	Resource use, mineral and metals	kg Sb eq. / kg product	3.53E-07	kg Sb eq. / kg product	4.66E-07
	Water use	m ³ world equiv. / kg product	0.36	m ³ world equiv. / kg product	0.84
	Environmental footprint, EF v3.0	eco points / kg product	1.20E-04	eco points / kg product	2.74E-04

More aggregated LCA endpoints are available on request.

Fundamentals

Life cycle assessment was calculated according to ISO 14040/44 (ISO, 2006; ISO/TC, 2006) using a mix of primary and secondary data including the Sphera MLC database version 2022.1. The analysis was performed with Sphera LCA for Experts Software (former GaBi 10.6). The total environmental footprint was calculated with the EFv3.0 method and the carbon footprint was calculated with the IPCC 2013 method. In accordance with the life cycle assessment approach, all processes within the cradle-to-gate system boundary were considered, 1 wt. % cut-off rule and no allocation were applied. The further processing, the use phase and the end-of-life phase of the material products are excluded from the system boundary. The LCA has undergone a critical review by an independent third party according to ISO 14040/44. Value(s) indicated are global average(s) and may be based on a varying number of manufacturing locations, including single location based only. A mass balance method according to ISCC PLUS standards is applied; the corresponding certification process has been initiated.

Miscellaneous

Mitsubishi Chemical Group's production sites for the manufacturing of this material are certified according to ISO 9001:2015 and ISO 14001:2015. Production sites are using electricity from Renewable Sources (RE).

Product name is a registered trademark of Mitsubishi Chemical Advanced Materials

This data sheet and any data and specifications presented on our website shall provide promotional and general information about the Engineering Plastic Products (the "Products") manufactured and offered by Mitsubishi Chemical Advanced Materials and shall serve as a preliminary guide. All data and descriptions relating to the Products are of an indicative nature only. Neither this data sheet nor any data and specifications presented on our website shall create or be implied to create any legal or contractual obligation.

The LCA data contained herein are provided to Mitsubishi Chemical Advanced Materials' best knowledge and in good faith. Such data may change from one production site to another and with time. Where available, data given are based on global averages. No warranties, express or implied, are given. Any liability of Mitsubishi Chemical Advanced Materials for the merchantability, fitness for a specific purpose, accuracy or completeness of such data is explicitly excluded.

Any illustration of the possible fields of application of the Products shall merely demonstrate the potential of these Products, but any such description does not constitute any kind of covenant whatsoever. Irrespective of any tests that Mitsubishi Chemical Advanced Materials may have carried out with respect to any Product, Mitsubishi Chemical Advanced Materials does not possess expertise in evaluating the suitability of its materials or Products for use in specific applications or products manufactured or offered by the customer respectively. The choice of the most suitable plastics material depends on available chemical resistance data and practical experience, but often preliminary testing of the finished plastics part under actual service conditions (right chemical, concentration, temperature and contact time, as well as other conditions) is required to assess its final suitability for the given application.

It thus remains the customer's sole responsibility to test and assess the suitability and compatibility of Mitsubishi Chemical Advanced Materials' Products for its intended applications, processes and uses, and to choose those Products which according to its assessment meet the requirements applicable to the specific use of the finished product. The customer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, or any consequence thereof, and shall verify its quality and other properties.

Copyright © 2023 The Mitsubishi Chemical Advanced Materials group of companies. All rights reserved. - Date of issue / revision: July 1, 2023